

SCOFIELD Pavecrafters

COMPANION PRODUCTS

LITHOCHROME® Color Hardener, (for areas subject to normal wear), and **EMERCHROME® Floor Hardener**, (for areas subject to heavier wear), are premium-quality, dry-shake colored hardeners used for imprinted concrete hardscapes and floors.

They add vibrant or subtle color to imprinted flatwork while providing a hard, durable, abrasion-resistant surface for pedestrian or vehicular traffic. Their rich finishing paste allows the production of sharp, clear, wear-resistant patterns, and for colder climates, their use increases the surface resistance of concrete to the damaging effects of freeze/thaw cycles and deicing salts. Both hardeners are available in 24 standard and designer colors. With a minimum order, virtually any custom color can be designed.


Concrete color-conditioned with a **CHROMIX® Admixture** may also be imprinted. Refer to the appropriate Tech-Data Bulletin A-104 **LITHOCHROME Color Hardener** A-204 **EMER-CHROME Floor Hardener**, or A-304 **CHROMIX Admixtures for Color-Conditioned Concrete** and Color Chart A-112 **LITHOCHROME Color Hardener** or A-312 **CHROMIX Admixtures**.

LITHOCHROME® Antiquing Release is a powdered, colored bond-breaker that helps prevent Pavecrafters tools from sticking to freshly imprinted concrete and marring its fragile surface. It is used with **LITHOCHROME Color Hardener** to create multicolored antiqued effects, producing imprinted concrete with an attractive, mottled patina and a naturally aged appearance Refer to Tech-Data Bulletin A-854 **LITHOCHROME Antiquing Release**.


LITHOCHROME® Chemstain™ creates uneven, variegated or translucent color effects on imprinted-concrete surfaces, much like the shadings of natural stone. The result is unique to each surface and cannot be duplicated by other coloring materials. Used over concrete colored with **LITHOCHROME Color Hardener** or a **CHROMIX Admixture**, a wider range of colors and special effects is obtainable. Refer to Tech-Data Bulletin A-414 **LITHOCHROME Chemstain** and Color Chart A-412 **LITHOCHROME Chemstain**.

CEMENTONE® Clear Sealer is a durable, environmentally compatible, clear, semigloss coating designed for sealing and protecting imprinted concrete hardscapes and floors. After applications of **LITHOCHROME Antiquing Release** or **LITHOCHROME Chemstain** initial sealing of and periodic maintenance with **CEMENTONE Clear Sealer** is required to preserve the variegated appearance and protect the surface during everyday use. Refer to Tech-Data Bulletin A-764 **CEMENTONE Clear Sealer**.


LITHOSEAL™ Trafficalk-3G™ is specifically designed for superior performance in areas subject to pedestrian and vehicular traffic. □ Tech-Data Bulletin S-404-3G **LITHOSEAL Trafficalk-3G** and Color Chart A-112 **LITHOCHROME Color Hardener**, A-312 **CHROMIX Admixtures** or S-302 **LITHOSEAL™ Joint Sealants**.




WOOD
P502, P512, & P522 Pine Plank
Request Pattern Sheet D-502




WOOD
P514 Cedar Parquet
Request Pattern Sheet D-514




MOORISH PAVER
P475 Interlocking
Request Pattern Sheet D-475




VICTORIAN PAVER
P483 Herringbone
Request Pattern Sheet D-483




COBBLESTONE
P355, P365, & P375 Interlocking
Request Pattern Sheet D-355



COBBLESTONE
P361 Running Bond
Request Pattern Sheet D-361



CLAY TILE
P461 Stacked Bond
Request Pattern Sheet D-451



FRACTURED SLATE
P338 Octagon and Square
Request Pattern Sheet D-338

CONCRETE PRODUCTS