



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product:	DECK-O-SEAL® 125 Setting Agent - Various Colors	Part Number: 4703000
Manufacturer:	W. R. MEADOWS, INC.	Address: 300 Industrial Drive
Telephone:	(847) 214-2100	Hampshire, Illinois 60140
Revision Date:	4/11/2019	In case of emergency, dial (800) 424-9300 (CHEMTREC)
Product Use:	Two Component Joint Sealar	

SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

HMIS	HAZARD STATEMENTS
Health 1	WARNING!
Flammability 1	May cause skin/eye irritation.
Reactivity 0	May cause an allergic skin reaction.
Personal Protection	PRECAUTIONARY STATEMENTS
	Avoid direct contact.
	Avoid breathing aerosols/sprays.

SECTION 3: HAZARDS COMPONENTS

Chemical Name:	CAS Number	% by Weight	SARA 313	Vapor Pressure (mm Hg@20°C)	LEL (@25°C)
1. Epoxy Resin	25068-38-6	5-15	No	N/E	N/E
2. Dimethylbenzyl Hydroperoxide	80-15-9	5-10	Yes	2	N/E
3. Titanium Dioxide	13463-67-7	0-30	No	N/E	N/E

N/E = Not Established N/A = Not Applicable

This product contains limestone. Limestone contains crystalline silica as a naturally occurring component. Exposure to silica is not expected to occur as the product is supplied as a solution. If product is dry/abraded, appropriate protective measures should be taken to control exposure to airborne silica.

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Move victim from exposure source. Flush eyes with water for fifteen minutes. If symptoms persist, seek medical attention.

SKIN CONTACT: Remove contaminated shoes/clothing. Wash affected areas with mild soap and water. If symptoms persist, seek medical attention.

INHALATION: Move victim from exposure source and treat symptoms. If symptoms persist, seek medical attention.

INGESTION: Seek immediate medical attention. Do not induce vomiting. If vomiting spontaneously occurs, keep the victim's head below the hips to prevent lung aspiration.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC: See Section Eleven for Symptoms/Effects.

SECTION 5: FIRE AND EXPLOSIVES HAZARDS

FLASHPOINT: > 210 °F

EXTINGUISHING MEDIA: Water fog, foam, dry chemical, and carbon dioxide

CHEMICAL/COMBUSTION HAZARDS: Carbon monoxide, carbon dioxide, and incomplete combustion products may be emitted.

PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Use of full fire protection ensemble with SCBA is recommended.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Evacuate area of unprotected personnel. Dike/contain spilled material. Take up with an appropriate absorbent and place in sealed/marked containers for proper disposal.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PROCEDURES: Avoid direct contact.

SAFE STORAGE: Keep containers closed when not in use. Store in cool/dry location.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name:	OSHA				ACGIH			
	PEL	PEL/CEILING	PEL/STEL	SKIN	TWA	TLV/CEILING	TLV/STEL	SKIN
1. Epoxy Resin	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E
2. Dimethyl Benzyl Hydroperoxide	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E
3. Titanium Dioxide*	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

N/E: Not Established

*Titanium Dioxide exposure limits not provided as materials are in suspension.

SAFETY DATA SHEET

Date of Preparation: 4/11/19

Page 2 of 2

4703000

Section 8 continued

ENGINEERING CONTROLS: None normally required under normal use conditions.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical-resistant gloves.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 250 °F	VAPOR DENSITY: >1 (Air=1)	% VOLATILE BY VOLUME: Not Applicable
EVAPORATION RATE: <1 (Ether=1)	pH LEVEL: N/A	% VOLATILE BY WEIGHT: Not Applicable
WEIGHT PER GALLON: 13.00	PRODUCT APPEARANCE: Heavy Liquid	VOC CONTENT: 0 g/L
ODOR: Mild Organic	ODOR THRESHOLD: N/D	MELTING/FREEZING POINT: N/D
FLASH POINT: See Section 5	FLAMMABILITY: N/D	UEL/LEL: N/D
VAPOR PRESSURE: N/D	RELATIVE DENSITY: N/D	SOLUBILITY: N/D
PARTITION COEFFICIENT: N/D	AUTOIGNITION TEMPERATURE: N/D	DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D		<i>N/D: Not Determined</i>

SECTION 10: STABILITY/REACTIVITY

STABILITY: Stable.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS AND MATERIALS TO AVOID: Oxidizing materials, strong acids, lead, copper, and their alloys, zinc, amines, polyamines, and polyamides under uncontrolled conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and incomplete combustion products.

SECTION 11: TOXICOLOGICAL INFORMATION

EYE CONTACT: Direct contact may cause mild to moderate irritation.

SKIN CONTACT: Direct contact may result in mild to moderate irritation. May cause a skin sensitization reaction in susceptible individuals. Skin sensitization may be temporary or permanent. Once an individual is diagnosed as sensitized, no further exposures can be permitted.

INHALATION: Not expected to be an exposure route under normal use conditions.

INGESTION: Not expected to be an exposure route under normal use conditions.

SIGNS AND SYMPTOMS: Symptoms of eye irritation include pain, tearing, redness, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and redness. Symptoms of respiratory irritation include runny nose, chest discomfort, shortness of breath, and reduced lung function. Symptoms of gastrointestinal irritation include sore throat, abdominal pain, nausea, vomiting, and diarrhea. Skin sensitization includes allergic dermatitis and is exhibited by rash, itching, hives, and swelling of extremities.

AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.

OTHER HEALTH EFFECTS: None recognized.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: Not Established

DEGRADABILITY: N/E

BIOACCUMULATIVE POTENTIAL: N/E

SOIL MOBILITY: N/E

OTHER ADVERSE EFFECTS: N/E

SECTION 13: WASTE DISPOSAL INFORMATION

WASTE DISPOSAL INFORMATION: Non-hazardous material for waste disposal purposes. Material mixed and set up can be landfill disposed.

SECTION 14: TRANSPORTATION INFORMATION

HAZARDOUS/NON-HAZARDOUS MATERIAL: Non-hazardous.

UN NUMBER: None.

HAZARD CLASS: None.

PACKING GROUP: None.

UN PROPER SHIPPING NAME: Not regulated.

ENVIRONMENTAL HAZARDS: Not determined.

BULK TRANSPORTATION INFORMATION: Not applicable; product is not shipped in bulk.

SPECIAL PRECAUTIONS: None recognized.

SECTION 15: REGULATORY INFORMATION

OTHER REGULATORY CONSIDERATIONS: None.

SECTION 16: OTHER INFORMATION

PREPARATION DATE: 4/11/2019

PREPARED BY: Dave Carey

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.